

## HAND OPERATED OIL PUMP

### Features:

- Economical outlook, materials and modeling are different than other machines in the market, stronger and more durable.
- Hand-pushing type, quite easy and convenient for movement.
- Light and portable type, operate manually and no electricity is needed.
- Suitable for all sorts of machinery, vehicles, airplanes, ships, etc.

The efficient instrument for infusing grease powerfully for lubrication & maintenance purpose.

- Suitable for lubricant oil, gear oil or general non-corrosive solvent, all can be infused into smoothly.
- Flow meter is available on optional accessories.



Code	Model	Capacity	Deliver Rate	Hose Length	N.W	G.W
3001	HO-25	25 L	70 cc/cycle	1/2" X 2 meter	7 kg	9 kg
3002	HO-25M	25 L	70 cc/cycle	1/2" X 2 meter	7 kg	9 kg

## HAND OPERATED GREASE PUMP

### Features:

- Most classic economical model. Material and production process are different than the others, made the quality better and more durable.
- Hand pushing type, quite easy to get moved.
- Grease packed in bulk of 20 liters can be poured inside.
- Quite portable and tube operated manually, no electricity is needed.
- Suitable for all sorts of machinery, vehicles, airplanes, ships, etc. The efficient instrument for infusing grease powerfully for lubrication & maintenance purpose.



## PNEUMATIC OPERATED GREASE PUMP

### Features:

- The barrel body is made of high-grade steel plate. It came to become durable and lasting even more after being made manually.
- Tank inner diameter 320mm, outer diameter 324mm, Tank inner height 438mm and outer height 440mm.
- Deluxe top opening flap design, suitable for 5 gallons tank of grease.
- Suitable for all sorts of machinery, vehicles, airplanes, ships, etc. The efficient instrument for infusing grease powerfully for lubrication & maintenance purpose.



Code	Model	Capacity	Max. Pressure	Shrink Rate	Deliver Rate	Hose Length	N.W (kg)	G.W (kg)
3025	HG-25	25 L	---	---	40cc/cycle	1/4"x1Wx2M	7	9
3026	AG-505	20 L	6~13 kg	1/45~1/55	1150cc/min	1/4"x2Wx3M	14.7	17.9

## PNEUMATIC OPERATED WASTE OIL SUCTION / DRAINER

### Features:

- Waste oil drainer with wheel-mounted tank, practical and functional, suitable for gravity draining of engine, gearbox and differential oil from all motor vehicles placed on auto lift or pit.
- Height adjustable collection bowl is mounted, enabling optimum positioning for work.
- Pneumatic drain the waste oil out under safe working pressure.

### Features:

- The air-operated drainers are ideal for quick engine oil change (means of suction) of any motor vehicle.
- The transparent chamber allows the quantity and quality of sucked oil to be checked immediately. Handy for draining over 10 liters.
- Equipped transparent chamber for observe the waste oil before extract into the reservoir.



PS-2081



PS-2097

Code	3050	3051
Model	PS-2081	PS-2097
Vacuum Degree	---	0 ~ 1 bar
Air Inlet Pressure	8 ~ 10 bar	8 ~ 10 bar
Tank Capacity	80 L	80 L
Suction Rate	---	1.5 ~ 2 L / min
Air Pressure For Oil Discharge	1 ~ 2 bar	1 ~ 2 bar
Oil Temperature Range	40 ~ 80°C	40 ~ 80°C
Measuring Glass	---	10 L
Oil Tank Application Temperature	< 80°C	< 80°C
Oil Tray	15 L	15 L
Dimension	500 X 420 X 915mm	500 X 420 X 890mm
N.W / G.W	22 / 25 kg	29 / 32 kg

*Important: Do not drain fluids, fuels or flammable liquids of any kind corrosive liquids.*

## PART WASHER

### Features:

- Fully enclosed electric pump re-circulates fluid for fast parts washing.
- 20 gallon steel tank has an operating level of 12 gallons.
- Self-latching cover provides optimum fire safety.
- Fluid is re-circulated through replaceable filter, and then sprayed on work piece through flexible nozzle.
- On/off switch with indicator light.
- Built-in drain, 220V/50 Hz water based solvent pump.
- 36 inch high overall on included stand.
- Convenient removable work shelf.

### Features:

- Big 40 gallon tank is designed for cleaning larger engine parts.
- 30 gallon solvent capacity.
- Fully enclosed electric pump re-circulates fluid for fast parts washing.
- Self-latching cover provides optimum fire safety.
- Fluid is re-circulated through replaceable filter, and then sprayed on work piece through flexible nozzle.
- On/off switch with indicator light.
- Built-in drain, 220V/50 Hz water based solvent pump.
- 36 inch high overall on included stand.
- Convenient removable work shelf.

20 GAL



TL-4001-20

40 GAL



TL-4001-40

Code	Model	Capacity	Dimension	N.W / G.W
3075	TL-4001-20	20 Gallon	790 X 550 X 320 mm	25 / 28 kg
3076	TL-4001-40	40 Gallon	1140 X 550 X 330 mm	42 / 45 kg

## ACCESSORIES

### 3900 OIL FLOW METER



### 3901 FOLLOWER PLATE



### 3902 OIL TRAY



### 3903 Z-SWIVEL CONNECTOR



### 3904 PNEUMATIC GREASE GUN

