



Palanca  
Handle



Palanca  
Handle



Mariposa  
Butterfly




Mariposa  
Butterfly



Roscar  
Threaded

Palanca Roscar H-H  
F-F Threaded



Ø	∩	A	B	h
3/8"	100	39	69	32
1/2"	100	48	78	36
3/4"	50	52	78	39
1"	50	62	100	50
1 1/4"	24	73	110	53
1 1/2"	12	84	110	58
2"	12	95	133	69
2 1/2"	6	126	160	83
3"	6	135	160	91
4"	2	167	160	103

### Components and materials

Body	- Brass (UNE-EN 12.164 - 12.165)
Ball	- Brass (UNE-EN 12.164 - 12.165)
Axis	- Brass (UNE-EN 12.164 - 12.165)
O-ring	- NBR
Sealing Joint	- PTFE
Handle	- Steel chromed
Butterfly	- Aluminium

### Note

- Guaranteed for the use of cold and hot water, and air.
- For fuel or aggressive liquids, please consult us.

### Work limits

- PN-25 bar (375 Lbs.)
- Maximum temperature 90°C

### Characteristics

- Low cost and high reliability.
- Fast close (1/4 turn).
- Double o-ring gasket in the axis.



Palanca  
Handle



Mariposa  
Butterfly



Cuadradillo  
Square handle



Cuadradillo Universal  
Universal square handle



Roscar  
Threaded



Soldar  
Soldering




Multicapa  
Multilayer



Polietileno Press-fitting  
Press-fitting polyethylene

### Palanca Roscar H-H

#### F-F Threaded



Ø	h	A	B	h
1/4"	100	40	75	42
3/8"	100	40	75	42
1/2"	100	48	95	48
3/4"	50	56	95	52
1"	50	65	104	58
1 1/4"	24	75	128	69
1 1/2"	12	85	128	74
2"	12	100	160	82
2 1/2"	6	130	227	110
3"	6	146	227	118
4"	2	178	227	129

#### Components and materials

Body / connector	- Brass (UNE-EN 12.164 - 12.165)
Ball	- Brass (UNE-EN 12.164 - 12.165)
Axis and packing-	Brass (UNE-EN 12.164 - 12.165)
Sealing Joint	- PTFE
Handle	- Chromed Steel
Butterfly	- Aluminium

#### Note

- Guaranteed for the use of cold and hot water, and air.
- For fuel or aggressive liquids, please consult us.

#### Work limits

- PN-30 bar (450 Lbs.)
- Maximum temperature 180°C at 10 kg/cm<sup>2</sup>  
100°C at 25 kg/cm<sup>2</sup>

#### Characteristics

- Low cost and high reliability.
- Fast close (1/4 turn).
- Packing gland in the axis.



Certificado DIN GOST