

# ELECTRO-HYDRALIC PIPE BENDERS

**DWG-4D**



| Model  | Max. Pressure (T) | Max. Stroke (mm) | Work Range (mm) | Bending Formers (in)     | Wall Thickness of Pipe (mm) | G.W. (kg) | Volume (cm) |
|--------|-------------------|------------------|-----------------|--------------------------|-----------------------------|-----------|-------------|
| DWG-4D | 21                | 370              | 21.5 - 108      | ½"¾"1"1¼"1½"2"2<br>½"3"4 | 2.75-6                      | 150       | 118*44*32   |

# PIPE BENDING MACHINE

## Hydraulic Type

| Model           | SWG-2A                                      | SWG-3B  |
|-----------------|---|---|
| Max. Pressure   | 45 mpa                                      | 50 mpa  |
| Max. Stroke     | 250 mm                                      | 320 mm  |
| Bending Angle   | $90^{\circ} \leq \beta < 180^{\circ}$       | $90^{\circ} \leq \beta < 180^{\circ}$             |
| Crimp Range     | $\varnothing 21.3 \sim \varnothing 60.0$ mm | $\varnothing 21.3 \sim \varnothing 88.5$ mm       |
| Wall Thickness  | 2.75~4.5 mm                                 | 2.75~5.0 mm                                       |
| Allocated Mould | 1/2", 3/4", 1",<br>1 1/4", 1 1/2", 2"       | 1/2", 3/4", 1", 1 1/4",<br>1 1/2", 2", 2 1/2", 3" |
| Weight          | 53 kg                                       | 117 kg  |



## Multi-Function Rolling Type



| Model               | DGWQJ-76B                     |
|---------------------|-------------------------------|
| Motor (1PH / 3PH)   | 1.1 kW                        |
| Circular Pipe Mould | 16,19,22,25,32,38,51,63,76 mm |
| Square Pipe Mould   | 16,19,22,25,30,38,40,50 mm    |
| Wall Thickness      | 0.5 - 2.0 mm                  |
| Weight              | 228 kg                        |

