



1. 40cc Gasoline engine

Reliable gasoline engine provides durable power to the pump.

2. Metal basket handle

Newly designed metal handle makes it easy to carry and brings flexible use.

3. Changeable outlet

1" and 1.5", round and square versions available. All outlets are now updated to aluminum version.

4. Aluminum volute

Advanced aluminum material makes the volute more efficient and durable.

5. Portable frame

Coated metal frame provides a steady positioning and maintains a glossy look. Light nylon frame also available.

| | |
|-----------------------------|---------------------------|
| Model | HZ-6510-25 |
| Engine | 1E40F-6 |
| Engine Type | 2-Stroke |
| Displacement | 40.2 cc |
| Power | 1.45 kw / 7000 rpm |
| Water Inlet/Outlet Diameter | 1" |
| Flow | 8 m³/h |
| Max. Head | 30 m |
| Suction Length | 8 m |
| Package Dimensions | 38 x 30 x 30 m |
| Weight | 7.4 kg |

Harz water pumps are designed for agricultural irrigation, gardening tasks and draining works. With versatile gasoline engines providing reliable power, you'll never worry about the heavy workload.



HZ-6511-25



HZ-6512-25



HZ-6513-25

| Model | HZ-6511-25 | HZ-6512-25 | HZ-6513-25 |
|---------------------|----------------------------|-----------------------------|----------------------------|
| Type | Self Priming | Self Priming | Self Priming |
| Flow | 8m³/h | 5m³/h | 19m³/h |
| Lift | 30 m | 30 m | 35 m |
| Suction Length | 8 m | 8 m | 8 m |
| Matched Engine | 1E44F-2A | 1E36F | 1E44F |
| Displacement | 51.7 cc | 30.5 cc | 52 cc |
| Max. Power | 1.4 kw / 6500 r/min | 0.81 kw / 6000 r/min | 1.4 kw / 7000 r/min |
| Inlet & Outlet Size | 1" / 1-1/2" inch | 1" inch | 1.5" inch |
| Fuel Tank Capacity | 1.2 L | 2.0 L | 1.0 L |
| Net Weight | 7 kg | 7.4 kg | 8.2 kg |
| Package | 38 x 30 x 33.5 cm | 35 x 24 x 40 cm | 60 x 35 x 31.5 cm |



HZ-6520-50



HZ-6520-75

| Model | HZ-6520-50 | HZ-6520-75 |
|-----------------------------|-----------------------|-----------------------|
| Max. Output | 7HP | 7HP |
| Water Inlet/Outlet Diameter | 2" | 3" |
| Max. Delivery Lift | 30 m | 30 m |
| Suction Height | 7 m | 7 m |
| Max. Water Displacement | 30 m ³ /hr | 60 m ³ /hr |
| Dimensions | 48.5 x 37.5 x 39.5 cm | 50.5 x 38.5 x 41.5 cm |
| Weight | 20 kg | 21 kg |



HZ-6525-50



HZ-6525-75



HZ-6525-50T

| Model | HZ-6525-50 | HZ-6525-75 | HZ-6525-50T |
|-----------------------------|-----------------------|-----------------------|-----------------------|
| Max. Output | 7HP | 15HP | 7.5HP |
| Water Inlet/Outlet Diameter | 2" | 3" | 2" |
| Max. Delivery Lift | 63 m | 85 m | 80 m |
| Suction Height | 7 m | 7 m | 7 m |
| Max. Water Displacement | 20 m ³ /hr | 60 m ³ /hr | 36 m ³ /hr |
| Dimensions | 41 x 39.5 x 39.5 cm | 55 x 49 x 52.5 cm | 49.5 x 39.5 x 42.5 cm |
| Weight | 25 kg | 53 kg | 25 kg |



HZ-50TH

SU-50 & SU-80



2" / 3"

2" & 3" pump head with pulley



**SNB-50P/Q
SNB-80P/Q**

| Model | HZ-50TH | SU-50 | SU-80 | SNB-50P/Q | SNB-80P/Q |
|---------------|-----------|-----------|-----------|-----------|-----------|
| Dia. In | 2" | 2" | 3" | 2" | 3" |
| Max. Capacity | 600 L/min | 500 L/min | 900 L/min | 500 L/min | 900 L/min |
| Max. Head | 80 m | 30 m | 30 m | 30 m | 30 m |